

Commonwealth of Australia

Gazette

No. TC 16/46, Wednesday, 30 November 2016 Published by the Commonwealth of Australia **TARIFF CONCESSIONS**

CONTENTS

TCO Applications	
TCOs Made	
Local Manufacturer Initiated - TCOs Revoked	
Website Update	16

The Commonwealth of Australia Tariff Concessions Gazette (the Tariff Concessions Gazette) is free of charge on the DIBP internet site at: http://www.border.gov.au

The Tariff Concessions Administration Section is located at 5 Constitution Ave Canberra City 2601

Contact details:

CUSTOMS ACT 1901 - NOTICE PURSUANT TO SECTION 269K(1) - APPLICATIONS MADE FOR TARIFF CONCESSION ORDERS

Applications have been lodged for Tariff Concession Orders for the goods described in the following TABLE.

Australian manufacturers who wish to contest the granting of a Tariff Concession Order for the goods described are invited to lodge a submission in writing in an approved form. Submissions must be lodged within 50 days of the date of publication of this Notice.

The operative date (Op.) and TC reference number follow the description of goods.

To assist local manufacturers, the use(s) to which the goods can be put follow the description of goods.

Objections to the making of TCO submission forms are available at

http://www.border.gov.au/Forms/Documents/b444.pdf

Contact: Email tarcon@border.gov.au

THE TABLE

_	of Goods including the ff Classification		Item Number Duty Rate
7210.49.00	COILS, non-alloy steel, hot rolled, zinc coated, complying with American Society for Testing and Materials Standard A653/A653M-11 (ASTM A653/A653M-11), having ALL of the following: (a) thickness NOT less than 3.60 mm and NOT greater than 6.0 mm; (b) width NOT less than 784 mm and NOT greater than 1 263 mm; (c) minimum yield strength NOT less than 175 Mpa; (d) minimum tensile strength NOT less than 280 Mpa; (e) inside diameter NOT less than 711 mm and NOT greater than 813 mm; (f) zinc coating mass NOT less than 0.040 kg/m2 per side; (g) weight NOT less than 14 metric tonnes; (h) chemical composition by weight of ALL of the following: (i) carbon content NOT greater than 0.20%; (ii) phosphorus content NOT greater than 0.03%; (iii) sulphur content NOT greater than 0.03%; (iv) aluminium content NOT greater than 0.25%; (vi) nickel content NOT greater than 0.25%; (vii) titanium content NOT greater than 0.04%; (viii) silicon content NOT greater than 0.45% Op. 25.10.16 Stated Use: Manufacture of pre-galvanised hollow structural sections	- TC 1663110	50
	Applicant: AUSTUBE MILLS PTY LTD		5%
8410.90.00	PARTS, HYDRAULIC TURBINE, being upper AND/OR lower draft tube cones Op. 07.11.16	- TC 1666770	50
	Stated Use: Draft tube cone is a part of the draft tube that is the water conduit from the runner to the outlet gate of a hydraulic turbine		
	Applicant: HYDRO-ELECTRIC CORPORATION		5%

	NC	TC 16/46, Wednesday, 30	NOV ZUI
	of Goods including the ff Classification	Schedule 4 Item General Duty	
8418.10.00	COMBINED REFRIGERATORS AND FREEZERS, whether OR not integrated, incorporating separate external doors, having an internal capacity NOT greater than 900 litres Op. 27.10.16	- TC 1663727	50
	Stated Use: For storage of food in domestic refrigerating and/or freezing environment		
	Applicant: ANDI-CO AUSTRALIA PTY LTD		5%
8418.21.00	REFRIGERATORS, underbench OR integrated, having an internal capacity NOT greater than 400 litres Op. 27.10.16	- TC 1663730	50
	Stated Use: For storage of food in domestic refrigerating environment		
	Applicant: ANDI-CO AUSTRALIA PTY LTD		5%
8418.40.00	FREEZERS, upright, having a capacity NOT greater than 400 litre Op. 27.10.16	s - TC 1663732	50
	Stated Use: For storage of food in domestic freezing environment		
	Applicant: ANDI-CO AUSTRALIA PTY LTD		5%
8479.82.00	PRINTING INK MIXING PLANT, programmable logic contolled, including ALL of the following: (a) mixers; (b) Clean-in-Place (CIP) operation; (c) motors; (d) tanks; (e) touch panel controller; (f) discharge pumps Op. 26.10.16	- TC 1663438	50
	Stated Use: The production of water based inks		
	Applicant: DIC AUSTRALIA PTY LTD		5%
8479.89.90	STRETCHING AND STAPLING CANVAS FRAMING MACHINES, pneumatic, including frame selection screen controls Op. 02.11.16	- TC 1665173	50
	Stated Use: For the mounting of canvases to picture frame bars		
	Applicant: PRIMA PRINTING PTY LTD		5%

Schedule 4 Item Number General Duty Rate

8504.40.90 INVERTERS, OFF-GRID OR ON-GRID, whether OR not skid OR shipping container mounted, whether OR not enclosed, having ALL of the following:

50

- (a) NOT greater than 2 rack mounted DC AND/OR AC inverter systems, each having:
 - (i) nominal rating NOT less than 60 kW and NOT greater than 2 800 kW;
 - (ii) rating NOT less than 50 kVA and NOT greater than 3 000 kVA;
 - (iii) current NOT less than 84 A and NOT greater than 4 800 A;
 - (iv) nominal AC coupling voltage NOT exceeding 480 VAC;
 - (v) frequency NOT less than 50 Hz and NOT greater than 60 Hz,
- (b) insulation monitoring relay;
- (c) control panel;
- (d) battery programmable logic controller AND microgrid controller

Op. 07.11.16 - TC 1666762

Stated Use:

Power storage unit for uninterrupted power supply to communities and industries, from the main grid supply, during both planned and unplanned power outages

Applicant: ABB AUSTRALIA PTY LTD

5%

CUSTOMS ACT 1901 - NOTICE PURSUANT TO SECTION 269R(1) - TARIFF CONCESSION ORDERS MADE

Tariff Concession Orders have been made for the goods described in the following TABLE.

The operative date (Op.) and TC reference No. follow the description of goods. Local manufacturers of substitutable goods may request the revocation of TCOs at any time.

Contact: Email tarcon@border.gov.au

THE TABLE

	of Goods including the ff Classification			Schedule 4 Item	Number
3808.92.00	FUNGICIDE, having an active ingredier Op. 23.08.16 De	nt of pyriofenone cc. date 22.11.16	- TC	1644661	50
3824.90.90	BLANKETS, incorporating heat pads Op. 31.08.16 De	c. date 28.11.16	- TC	1647352	50
3907.99.90	POLYESTERS, amorphous linear saturate Op. 30.08.16 De	ed c. date 28.11.16	- TC	1646867	50
3923.30.00	PREFORMS, BOTTLE, polyethylene tereph ALL of the following: (a) inner neck diameter NOT less the greater than 46.15 mm; (b) neck outer diameter NOT less the greater than 55.40 mm; (c) neck thread diameter NOT less the greater than 55.45 mm Op. 31.08.16 De	han 45.85 mm and NOT	- TC	1647286	50
6806.90.90	PANELS, HEAT INSULATION, microporous, insulating temperature capacity NOT 1 Celsius Op. 07.09.16 De		- TC	1649255	50
7224.90.00	DISCS AND/OR SQUARES, alloy steel, ho tempered, having ALL of the following (a) diameter NOT less than 295 mm a 2 005 mm; (b) thickness NOT less than 1.6 mm greater than 12.4 mm; (c) carbon content NOT less than 0.0 (d) chrome content NOT less than 0.0 (e) flatness deviation NOT greater Op. 07.09.16	g: and NOT greater than and NOT greater than NOT .70%; .30%;	- TC	1649262	50
7326.90.90	DAMPENERS, SUBSEA AND/OR DOWNHOLE, ac whether OR not assembled Op. 31.08.16 De	coustic, non-mechanical,	- TC	1647346	50
8210.00.00	COFFEE MAKERS, ESPRESSO, manually oper carry cases Op. 06.09.16 De	erated, with OR without	- TC	1648860	50
8302.42.00	DRAWER RUNNERS, metal, extendable, si the following: (a) load carrying capacity NOT grea (b) ball cages Op. 06.09.16 De	-	- TC	1648704	50
8428.90.00	BOTTLE AND/OR CAN RECYCLING MACHINES, OR without EITHER of the following: (a) compactor; (b) storage chamber Op. 31.08.16 De	, including a sorter, with	- TC	1647138	50

	of Goods including the ff Classification		Schedule 4 Item	n Number
8465.92.00	INSULATION BOARD TRIMMING AND/OR SQU Op. 02.09.16 De		- TC 1648420	50
8479.82.00	MIXERS, PLOUGH SHEAR, programmable lactuated, including ALL of the following all of the following showed including shows		- TC 1649258	50
8479.89.90	INSULATION BOARD PRODUCTION LINE, in (a) unwinders; (b) pouring table with a vacuum ex (c) double belt conveyor; (d) conditioning heated conveyor; (e) safety system, having ALL of t (i) alarm; (ii) control panel; (iii) gas sensors; (iv) fume extractor Op. 26.08.16	tractor;	- TC 1646110	50
8479.89.90	SCRAPERS, SEWAGE OR WASTE WATER TREA sludge removal system, having ALL of (a) scraper flights; (b) chains; (c) sprockets; (d) gear motor drives; (e) wear shoes; (f) rails; (g) head shafts; (h) collector chain tensioning dev	TIMENT, with OR without the following:		50
8709.11.00	GUIDED CARTS, battery powered, programagnetic guided	cammable logic controlled,	- TC 1647775	50

transit provisions apply

CUSTOMS ACT 1901 - NOTICE PURSUANT TO SECTION 269SE(1) - AUSTRALIAN INDUSTRY INITIATED - TARIFF CONCESSION ORDERS REVOKED

The Tariff Concession Orders for the goods described in the following TABLE have been revoked.

Contact: Email tarcon@border.gov.au

THE TABLE

Description of Goods including the Customs Tariff Classification			Schedule 4 Item Number Last Date of Effect	
4016.91.00	PAVERS, rubber, imitation masonry powder coating, of edging, having BOTH of the following: (a) length NOT greater than 550mm; (b) thickness NOT greater than 20 mm Op. 22.03.12 Dec. date 15.06.	chamfered top	50 25.10.16	
	Substitutable goods produced in Australia in the or course of business by A1 Rubber Pty Ltd, Yatala, Q1 transit provisions apply	dinary	. 1209340	
4016.91.00	PAVERS, RUBBER, powder coated, including ALL of the (a) length NOT greater than 1 050 mm; (b) thickness NOT greater than 20 mm; (c) bevelled edges Op. 07.08.13 Dec. date 04.11.	e following:	50 25.10.16	
	Substitutable goods produced in Australia in the or course of business by Al Rubber Pty Ltd, Yatala, Ql transit provisions apply	dinary	, 1320347	
7208.26.00	STEEL, flat rolled, non-alloy, hot rolled, pickled, in coils, complying with Japanese Industrial Standa (3131), grades SPHD OR SPHE, having ALL of the following in the strength NOT less than 270 MPa; (b) elongation NOT less than 32%; (c) in ANY of the following sizes: (i) thickness 3.00 mm and width 760 mm; (ii) thickness 3.00 mm and width 1 119 mm; (iii) thickness 3.50 mm and width 1 145 mm; (iv) thickness 4.00 mm and width 875 mm; (v) thickness 4.00 mm and width 970 mm; (vi) thickness 4.00 mm and width 1 070 mm;	ard G3131 (JIS Lowing: mm; mm;	50 23.10.16	
	For the purposes of this Order, tolerances allowable specification (c) are:	e for		
	(a) thickness +/- 10% (b) width +/- 1% Op. 04.04.13 Dec. date 24.06.	13 - TC	: 1311527	
	Substitutable goods produced in Australia in the or course of business by Bluescope Steel Ltd, Port Ken transit provisions apply			

Schedule 4 Item Number Last Date of Effect

7208.26.00 STEEL, flat-rolled, non alloy, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3113 (JIS G3113), grade SAPH440, having ALL of the following:

50 23.10.16

- (a) yield strength NOT less than 305 MPa;
- (b) tensile strength NOT less than 440 MPa;
- (c) elongation NOT less than 29%;
- (d) in ANY of the following sizes:
 - (i) thickness 3.40 mm and width 985 mm;
 - (ii) thickness 3.50 mm and width 805 mm;
 - (iii) thickness 4.00 mm and width 1 210 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/-1%

Op. 04.04.13

Dec. date 24.06.13

- TC 1311719

Substitutable goods produced in Australia in the ordinary course of business by Bluescope Steel, Port Kembla, NSW. In transit provisions apply

7208.27.00

STEEL, flat rolled, iron OR non-alloy, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3131 (JIS G3131), grades SPHC OR SPHD OR SPHE, having ALL of the following:

50 23.10.16

- (a) tensile strength NOT less than 270 MPa;
- (b) total elongation NOT less than 27%;
- (c) in ANY of the following sizes:
 - (i) thickness 1.20 mm and width 610 mm;
 - (ii) thickness 1.20 mm and width 820 mm;
 - (iii) thickness 1.20 mm and width 838 mm;
 - (iv) thickness 1.40 mm and width 690 mm;
 - (v) thickness 1.40 mm and width 1 050 mm; (vi) thickness 1.40 mm and width 1 080 mm;
 - (vii) thickness 1.40 mm and width 1 150 mm;
 - (viii) thickness 1.40 mm and width 1 390 mm;
 - (ix) thickness 1.60 mm and width 1 010 mm;
 - (x) thickness 1.90 mm and width 1 110 mm;
 - (xi) thickness 1.90 mm and width 1 340 mm; (xii) thickness 1.90 mm and width 1 360 mm

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 14.03.13

Dec. date 03.06.13

- TC 1309208

Description of Goods including the

Schedule 4 Item Number

```
Customs Tariff Classification
                                                                                          Last Date of Effect
7208.27.00
              STEEL, flat rolled, non-alloy, hot rolled, pickled, not coated,
                                                                                                        50
              in coils, complying with Japanese Industrial Standard G3131 (JIS
                                                                                                     23.10.16
              G3131), grades SPHD OR SPHE, having ALL of the following:
                (a) tensile strength NOT less than 270 MPa;
                (b) elongation NOT less than 32%;
                (c) in ANY of the following sizes:
                          (i) thickness 1.60 mm and width 620 mm;
                          (ii) thickness 1.60 mm and width 658 mm;
                         (iii) thickness 1.60 mm and width 710 mm;
                          (iv) thickness 1.60 mm and width 929 mm:
                          (v) thickness 1.60 mm and width 930 mm;
                          (vi) thickness 1.60 mm and width 950 mm;
                         vii) thickness 1.60 mm and width 1 030 mm;
                       (viii) thickness 1.60 mm and width 1 035 mm;
                          (ix) thickness 1.60 mm and width 1 090 mm;
                          (x) thickness 1.60 mm and width 1 110 mm;
                          (xi) thickness 1.80 mm and width 1 000 mm;
                        (xii) thickness 1.90 mm and width 730 mm;
                       (xiii) thickness 1.90 mm and width 760 mm;
                         (xiv) thickness 1.90 mm and width 825 mm;
                         (xv) thickness 1.90 mm and width 905 mm;
```

(xxvi) thickness 2.00 mm and width 1 024 mm; (xxvii) thickness 2.00 mm and width 1 140 mm; (xxviii) thickness 2.00 mm and width 1 210 mm; (xxix) thickness 2.20 mm and width 785 mm; (xxx) thickness 2.20 mm and width 970 mm; (xxxi) thickness 2.20 mm and width 1 155 mm; (xxxii) thickness 2.20 mm and width 1 175 mm; (xxxii) thickness 2.20 mm and width 1 175 mm;

(xxxiii) thickness 2.50 mm and width 1 020 mm; (xxxiv) thickness 2.50 mm and width 1 160 mm

(xvi) thickness 1.90 mm and width 940 mm; (xvii) thickness 1.90 mm and width 955 mm; (xviii) thickness 1.90 mm and width 1 010 mm; (xix) thickness 1.90 mm and width 1 030 mm; (xx) thickness 1.90 mm and width 1 050 mm; (xxi) thickness 1.90 mm and width 1 060 mm; (xxii) thickness 1.90 mm and width 1 110 mm; (xxiii) thickness 1.90 mm and width 1 125 mm; (xxiv) thickness 1.90 mm and width 1 120 mm; (xxiv) thickness 2.00 mm and width 607 mm;

For the purposes of this Order, tolerances allowable for specification (c) are:

```
(a) thickness +/- 10% (b) width +/- 1% Op. 04.04.13
```

Dec. date 24.06.13

- TC 1311524

Schedule 4 Item Number Last Date of Effect

7208.27.00 STEEL, flat rolled, non-alloy, hot rolled, pickled, not coated, 50 in coils, complying with Japanese Industrial Standard G3113 (JIS 23.10.16 G3113), grade SAPH440, having ALL of the following: (a) yield strength NOT less than 305 MPa; (b) tensile strength NOT less than 440 MPa; (c) elongation NOT less than 29%; (d) in ANY of the following sizes: (i) thickness 1.60 mm and width 655 mm; (ii) thickness 1.60 mm and width 740 mm; (iii) thickness 1.60 mm and width 762 mm: (iv) thickness 1.60 mm and width 780 mm; (v) thickness 1.60 mm and width 800 mm; (vi) thickness 1.60 mm and width 825 mm; (vii) thickness 1.60 mm and width 860 mm; (viii) thickness 1.60 mm and width 930 mm; (ix) thickness 1.60 mm and width 1 009 mm; (x) thickness 1.60 mm and width 1 058 mm; (xi) thickness 1.70 mm and width 950 mm; (xii) thickness 1.70 mm and width 959 mm; (xiii) thickness 1.95 mm and width 950 mm; (xiv) thickness 1.95 mm and width 1 185 mm; (xv) thickness 2.00 mm and width 760 mm; (xvi) thickness 2.00 mm and width 766 mm; (xvii) thickness 2.00 mm and width 860 mm; (xviii) thickness 2.00 mm and width 955 mm; (xix) thickness 2.00 mm and width 1 090 mm; (xx) thickness 2.50 mm and width 1 135 mm For the purposes of this Order, tolerances allowable for specification (d) are:

Substitutable goods produced in Australia in the ordinary course of business by Bluescope Steel Ltd, Port Kembla, NSW. In transit provisions apply

7209.16.00 STEEL, flat rolled, non-alloy, cold rolled, not coated, in coils, having ALL of the following:

50 23.10.16

- (a) yield strength NOT greater than 250 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) elongation NOT less than 35%;
- (d) thickness 1.20 mm and width 1 748 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

(a) thickness +/- 10%

(a) thickness +/- 10% (b) width +/- 1% Op. 04.04.13

(b) width +/- 1%

Op. 27.03.13

Dec. date 17.06.13

Dec. date 24.06.13

- TC 1310748

- TC 1311717

Schedule 4 Item Number

```
Last Date of Effect
7209.16.00
              STEEL, flat rolled, non-alloy, cold rolled, not coated,
                                                                                                        50
              in coils, having ALL of the following:
                                                                                                     23.10.16
                (a) yield strength NOT greater than 250 MPa;
                (b) tensile strength NOT less than 250 MPa;
                (c) elongation NOT less than 35%;
                (d) in ANY of the following sizes:
                          (i) thickness 1.15 mm and width 715 mm;
                          (ii) thickness 1.15 mm and width 740 mm;
                         (iii) thickness 1.15 mm and width 780 mm;
                         (iv) thickness 1.15 mm and width 890 mm;
                           (v) thickness 1.15 mm and width 1 089mm;
                          (vi) thickness 1.15 mm and width 1 110 mm;
                         (vii) thickness 1.15 mm and width 1 190 mm;
                       (viii) thickness 1.20 mm and width 870 mm;
                          (ix) thickness 1.20 mm and width 1 175 mm;
                          (x) thickness 1.20 mm and width 1 230 mm;
                          (xi) thickness 1.35 mm and width 1 020 mm;
                        (xii) thickness 1.35 mm and width 1 185 mm;
                       (xiii) thickness 1.35 mm and width 1 525 mm;
                         (xiv) thickness 1.40 mm and width 770 mm;
                         (xv) thickness 1.40 mm and width 870 mm;
                        (xvi) thickness 1.40 mm and width 955 mm;
```

(xvii) thickness 1.55 mm and width 800 mm; (xviii) thickness 1.55 mm and width 801 mm; (xix) thickness 1.55 mm and width 1 380 mm; (xx) thickness 1.60 mm and width 790 mm; (xxi) thickness 1.60 mm and width 1 060 mm; (xxii) thickness 1.80 mm and width 910 mm; (xxii) thickness 1.80 mm and width 1 080 mm; (xxiv) thickness 1.80 mm and width 1 090 mm; (xxv) thickness 1.80 mm and width 1 135 mm; (xxv) thickness 1.80 mm and width 1 135 mm; (xxv) thickness 1.95 mm and width 770 mm; (xxvii) thickness 1.95 mm and width 1 200 mm

```
(a) thickness +/- 10% (b) width +/- 1% Op. 09.04.13
```

Dec. date 24.06.13

- TC 1312160

Schedule 4 Item Number Last Date of Effect

```
7209.17.00
              STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not
                                                                                                       5.0
              coated, in coils, having ALL of the following;
                                                                                                    06.11.16
                (a) yield strength NOT greater than 210 MPa;
                (b) tensile strength NOT less than 250 MPa;
                (c) total elongation NOT less than 40%;
                (d) in ANY of the following sizes:
                         (i) thickness 0.75 mm and width 1 150 mm;
                         (ii) thickness 0.75 mm and width 1 435 mm;
                       (iii) thickness 0.75 mm and width 1 565 mm;
                         (iv) thickness 0.75 mm and width 1 640 mm:
                         (v) thickness 0.75 mm and width 1 700 mm;
                         (vi) thickness 0.80 mm and width 1 220 mm;
                       (vii) thickness 0.80 mm and width 1 565 mm;
                      (viii) thickness 0.80 mm and width 1 580 mm;
                         (ix) thickness 0.80 mm and width 1 584 mm;
                         (x) thickness 0.80 mm and width 1 585 mm;
                         (xi) thickness 0.80 mm and width 1 590 mm;
                       (xii) thickness 0.80 mm and width 1 625 mm;
                      (xiii) thickness 0.85 mm and width 1 730 mm
              For the purposes of this Order, tolerances allowable for
              specification (d) are:
              (a) thickness +/- 10%
              (b) width +/-1%
              Op. 24.12.12
                                                 Dec. date 18.03.13
                                                                                  - TC 1248927
              Substitutable goods produced in Australia in the ordinary
              course of business by Bluescope Steel Ltd, Port Kembla, NSW. In
              transit provisions apply
7209.17.00
              STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not
                                                                                                        50
              coated, in coils, having ALL of the following:
                                                                                                    06.11.16
                (a) yield strength NOT less than 185 MPa;
                (b) tensile strength NOT less than 340 MPa;
                (c) total elongation NOT less than 32%;
                (d) in ANY of the following sizes:
                         (i) thickness 0.70 mm and width 1 235 mm;
                         (ii) thickness 0.70 mm and width 1 350 mm;
                       (iii) thickness 0.70 mm and width 1 425 mm;
                        (iv) thickness 0.70 mm and width 1 450 mm;
                         (v) thickness 0.70 mm and width 1 453 mm;
                         (vi) thickness 0.70 mm and width 1 470 mm;
                        (vii) thickness 0.70 mm and width 1 485 mm;
                      (viii) thickness 0.70 mm and width 1 510 mm;
                         (ix) thickness 0.70 mm and width 1 520 mm;
                         (x) thickness 0.70 mm and width 1 530 mm;
                         (xi) thickness 0.75 mm and width 1 390 mm;
                       (xii) thickness 0.75 mm and width 1 525 mm;
                      (xiii) thickness 0.75 mm and width 1 555 mm;
                       (xiv) thickness 0.75 mm and width 1 710 mm;
                        (xv) thickness 0.75 mm and width 1 740 mm;
                       (xvi) thickness 0.75 mm and width 1 800 mm;
                      (xvii) thickness 0.80 mm and width 1 435 mm;
                     (xviii) thickness 0.80 mm and width 1 585 mm
              For the purposes of this Order, tolerances allowable for
              specification (d) are:
              (a) thickness +/- 10%
              (b) width +/-1%
              Op. 24.12.12
                                                 Dec. date 18.03.13
                                                                                  - TC 1248928
```

Schedule 4 Item Number Last Date of Effect

```
7209.17.00
              STEEL, flat rolled, non-alloy, cold rolled, not
                                                                                                        50
              coated, in coils, having ALL of the following:
                                                                                                     06.11.16
                (a) yield strength NOT greater than 250 MPa;
                (b) tensile strength NOT less than 270 MPa;
                (c) elongation NOT less than 35%;
                (d) in ANY of the following sizes:
                        (i) thickness 0.60 mm and width 1 700 mm;
                        (ii) thickness 0.60 mm and width 1 710 mm;
                       (iii) thickness 0.60 mm and width 1 780 mm;
                       (iv) thickness 0.65 mm and width 1.560 mm:
                         (v) thickness 0.70 mm and width 1 600 mm;
                        (vi) thickness 0.80 mm and width 1 730 mm;
                       (vii) thickness 0.80 mm and width 1 775 mm;
                     (viii) thickness 1.00 mm and width 1 588 mm \,
              For the purposes of this Order, tolerances allowable for
              specification (d) are:
              (a) thickness +/- 10%
              (b) width +/-1%
                                                                                  - TC 1310743
              Op. 27.03.13
                                                 Dec. date 17.06.13
              Substitutable goods produced in Australia in the ordinary
              course of business by Bluescope Steel Ltd, Port Kembla, NSW. In
              transit provisions apply
7209.17.00
              STEEL, flat rolled, non-alloy, cold rolled, not coated,
                                                                                                        50
              in coils, having ALL of the following:
                                                                                                     06.11.16
                (a) yield strength NOT greater than 250 MPa;
                (b) tensile strength NOT less than 250 MPa;
                (c) elongation NOT less than 35%;
                (d) in ANY of the following sizes:
                          (i) thickness 0.67 mm and width 1 050 mm;
                          (ii) thickness 0.67 mm and width 1 065 mm;
                         (iii) thickness 0.67 mm and width 1 080 mm;
                         (iv) thickness 0.70 mm and width 915 mm;
                           (v) thickness 0.70 mm and width 1 020 mm;
                          (vi) thickness 0.70 mm and width 1 050 mm;
                         (vii) thickness 0.70 mm and width 1 230 mm;
                        (viii) thickness 0.70 mm and width 1 275 mm;
                          (ix) thickness 0.70 mm and width 1 285 mm;
                           (x) thickness 0.70 mm and width 1 400 mm;
                          (xi) thickness 0.72 mm and width 840 mm;
                         (xii) thickness 0.72 mm and width 1 030 mm;
                       (xiii) thickness 0.72 mm and width 1 500 mm;
                         (xiv) thickness 0.75 mm and width 1 150 mm;
                          (xv) thickness 0.75 mm and width 1 220 mm;
                         (xvi) thickness 0.75 mm and width 1 370 mm;
                       (xvii) thickness 0.75 mm and width 1 410 mm;
                       (xviii) thickness 0.75 mm and width 1 420 mm;
                         (xix) thickness 0.75 mm and width 1 425 mm;
                         (xx) thickness 0.75 mm and width 1 435 mm;
                         (xxi) thickness 0.75 mm and width 1 450 mm;
                       (xxii) thickness 0.75 mm and width 1 455 mm;
                       (xxiii) thickness 0.75 mm and width 1 490 mm;
                       (xxiv) thickness 0.76 mm and width 660 mm;
                        (xxv) thickness 0.76 mm and width 675 mm;
                       (xxvi) thickness 0.76 mm and width 1 080 mm;
                       (xxvii) thickness 0.76 mm and width 1 120 mm;
                      (xxviii) thickness 0.76 mm and width 1 420 mm;
                       (xxix) thickness 0.80 mm and width 600 mm;
                        (xxx) thickness 0.80 mm and width 620 mm;
                       (xxxi) thickness 0.80 mm and width 660 mm;
```

(Continued on next page)

(xxxii) thickness 0.80 mm and width 785 mm; (xxxiii) thickness 0.80 mm and width 850 mm; (xxxiv) thickness 0.80 mm and width 900 mm; (xxxv) thickness 0.80 mm and width 1 010 mm; (xxxvi) thickness 0.80 mm and width 1 140 mm; (xxxvii) thickness 0.80 mm and width 1 220 mm; (xxxviii) thickness 0.80 mm and width 1 270 mm;

Schedule 4 Item Number Last Date of Effect

```
(Continued from previous page)
```

```
(xxxix) thickness 0.80 mm and width 1 570 mm;
   (x1) thickness 0.80 mm and width 1 584 mm;
   (xli) thickness 0.85 mm and width 995 mm;
 (xlii) thickness 0.85 mm and width 1 140 mm;
 (xliii) thickness 0.85 mm and width 1 300 mm;
 (xliv) thickness 0.85 mm and width 1 484 mm;
  (xlv) thickness 0.90 mm and width 1 060 mm;
 (xlvi) thickness 0.95 mm and width 820 mm:
(xlvii) thickness 0.95 mm and width 930 mm;
(xlviii) thickness 0.95 mm and width 990 mm;
 (xlix) thickness 0.95 mm and width 1 100 mm;
    (1) thickness 0.95 mm and width 1 105 mm;
   (li) thickness 0.95 mm and width 1 130 mm;
  (lii) thickness 0.95 mm and width 1 170 mm;
  (liii) thickness 0.95 mm and width 1 290 mm;
  (liv) thickness 0.95 mm and width 1 302 mm;
   (lv) thickness 0.95 mm and width 1 770 mm;
   (lvi) thickness 1.00 mm and width 765 mm
```

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 09.04.13

Dec. date 24.06.13

- TC 1312159

Substitutable goods produced in Australia in the ordinary course of business by Bluescope Steel LTD, Port Kembla, NSW. In transit provisions apply

7210.49.00

STEEL, flat rolled, non-alloy steel, hot dipped galvannealed zinc coated, in coils, having ALL of the following:

50 06.11.16

- (a) yield strength NOT greater than 210 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 40%;
- (d) total coating mass NOT less than 30 g/m2 and NOT greater than 70 g/m2 on each side;
- (e) in ANY of the following sizes:
 - (i) thickness 0.75 mm and width 1 390 mm;
 - (ii) thickness 0.75 mm and width 1 450 mm;
 - (iii) thickness 0.75 mm and width 1 475 mm;
 - (iv) thickness 0.75 mm and width 1 530 mm;
 - (v) thickness 0.75 mm and width 1 565 mm; (vi) thickness 0.75 mm and width 1 640 mm;
 - (vii) thickness 0.76 mm and width 1 220 mm;
 - (viii) thickness 0.80 mm and width 1 350 mm;
 - (ix) thickness 0.95 mm and width 820 mm;
 - (x) thickness 1.00 mm and width 624 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/-1%

Op. 24.12.12

Dec. date 18.03.13

- TC 1248929

Schedule 4 Item Number Last Date of Effect

7210.49.00 STEEL, flat rolled, non-alloy steel, hot dipped galvannealed 5.0 zinc coated, in coils, having ALL of the following: 06.11.16 (a) yield strength NOT less than 190 MPa; (b) tensile strength NOT less than 340 MPa; (c) total elongation NOT less than 32%; (d) total coating mass NOT less than 30 $\ensuremath{\mathrm{g}/\mathrm{m2}}$ and NOT greater than 70 g/m2 on each side; (e) in ANY of the following sizes: (i) thickness 0.70 mm and width 865 mm; (ii) thickness 0.70 mm and width 980 mm; (iii) thickness 0.70 mm and width 1 225 mm; (iv) thickness 0.70 mm and width 1 244 mm; (v) thickness 0.70 mm and width 1 300 mm; (vi) thickness 0.70 mm and width 1 350 mm; (vii) thickness 0.70 mm and width 1 370 mm; (viii) thickness 0.70 mm and width 1 400 mm; (ix) thickness 0.70 mm and width 1 410 mm; (x) thickness 0.70 mm and width 1 455 mm; (xi) thickness 0.70 mm and width 1 500 mm; (xii) thickness 0.70 mm and width 1 585 mm; (xiii) thickness 0.70 mm and width 1 710 mm; (xiv) thickness 0.70 mm and width 1 720 mm; (xv) thickness 0.65 mm and width 865 mm; (xvi) thickness 0.65 mm and width 1 800 mm; (xvii) thickness 1.00 mm and width 1 160 mm For the purposes of this Order, tolerances allowable for specification (e) are: (a) thickness +/- 10% (b) width +/-1% Op. 24.12.12 - TC 1248930 Dec. date 18.03.13 Substitutable goods produced in Australia in the ordinary course of business by Bluescope Steel Ltd, Port Kembla, NSW. In

7210.49.00

STEEL, flat rolled, non-alloy, hot dipped galvannealed zinc coated, in coils, having ALL of the following:

50 06.11.16

- (a) yield strength NOT less than 190 MPa;
- (b) tensile strength NOT less than 340 MPa;
- (c) elongation NOT less than 32%;
- (d) coating mass NOT less than 30 g/m2 and NOT greater than 70 g/m2 on each side;
- (e) in EITHER of the following sizes:
 - (i) thickness 0.70 mm and width 1 740 mm;
 - (ii) thickness 1.00 mm and width 1 225 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

(a) thickness +/- 10%

transit provisions apply

(b) width +/- 1%

Op. 04.03.13

Dec. date 13.05.13

- TC 1307948

WEBSITE UPDATE

The Department has modernised its website with a new searchable online format for tariffrelated information for importers.

The fresh, new look applies to:

The Working Tariff: This is an online version of the Combined Australian Customs Tariff Nomenclature and Statistical Classification. It incorporates the Harmonized Commodity Description and Coding System, which define internationally-accepted tariff classifications for traded goods. It also records Australian rates of customs duties for imported goods, and related statistical codes from the Australian Bureau of Statistics.

http://www.border.gov.au/Busi/cargo-support-trade-and-goods/importing-goods/tariff-classification-of-goods/current-tariff-classification-online-version

Tariff Concession Orders (TCOs): More than 15,000 TCOs are now easily searchable, and more accessible for importers and manufacturers. http://www.border.gov.au/Busi/domestic-manufacturers-and-importers/list-of-tariff-concession-orders

The website changes include, for the first time, a page dedicated to the interests of domestic manufacturers and importers, who are key stakeholders of the Tariff Concession System. http://www.border.gov.au/Domesticmanufacturersandproducers/

Any feedback would be welcome to tarcon@border.gov.au